

Papers related to the application of Ring Shear Testers RST-01 or RST-XS

If you know a paper that should be included here, please be so kind and keep us informed. Thank you.

Papers are listed in random order.

- [1] Tissen, C., Woertz, K., Breikreutz, J., Kleinebudde, P.: Development of mini-tablets with 1 mm and 2 mm diameter, *International Journal of Pharmaceutics* 416 (2011) 1, pp. 164-170
- [2] Chatteraj, S., Shi, L., Sun, C.C.: Profoundly improving flow properties of a cohesive cellulose powder by surface coating with nano-silica through comilling, *Journal of Pharmaceutical Sciences* 100 (2011) 11, pp. 4943-4952
- [3] Althaus, T.O., Windhab, E.J.: Characterization of wet powder flowability by shear cell measurements and compaction curves, *Powder Technology* (2011) (in press)
- [4] Mullarney, M.P., Beach, L.E., Rajesh, N.D., Langdon, B.A., Polizzi, M., Blackwood, D.O.: Applying dry powder coatings to pharmaceutical powders using a comil for improving powder flow and bulk density, *Powder Technology* 212 (2012), pp. 397-402
- [5] Landi, G., Barletta, D., Poletto, M.: Modelling and experiments on the effect of air humidity on the flow properties of glass powders, *Powder Technology* 207 (2011), pp. 437-443
- [6] Shi, L., Chatteraj, S., Sun, C.C.: Reproducibility of flow properties of microcrystalline cellulose – Avicel PH102, *Powder Technol.* 212 (2011), pp. 253-257
- [7] Shi, L., Feng, Y., Sun, C.C.: Origin of profound changes in powder properties during wetting and nucleation stages of high-shear wet granulation of microcrystalline cellulose, *Powder Technol.* 208 (2011), pp. 663-668
- [8] Shi, L., Feng, Y., Sun, C.C.: Massing in high-shear wet granulation can simultaneously improve powder flow and deteriorate powder compaction: A double-edged sword, *European J. of Pharm. Sci.* 43 (2011), pp. 50-56
- [9] Roth, C., Künsch, Z., Sonnenfeld, A., von Rohr, P.R.: Plasma surface modification of powders for pharmaceutical applications, *Surface & Coatings Technol.* 205 (2011), pp. S597-S600
- [10] Djuric, D., Van Melkebeke, B., Kleinebudde, P., Remon, J.P., Vervaet, C.: Comparison of two twin-screw extruders for continuous granulation, *European J. of Pharmaceutics and Biopharmaceutics* 71 (2009), pp. 155-160
- [11] Watling, C.P., Elliott, J.A., Cameron, R.E.: Entrainment of lactose inhalation powders: A study using laser diffraction, *European J. of Pharmaceutical Sciences* 40 (2010), pp. 352-358
- [12] Yu, W., Muteki, H., Zhang, L., Kim, G.: Prediction of bulk powder flow performance using comprehensive particle size and particle shape distributions, *J. Pharmaceutical Sciences* 100 (2011) 1, pp. 284-293,
- [13] Palzer, S.: The effect of glass transition on the desired and undesired agglomeration of amorphous food powders, *Chem. Eng. Sci.* 60 (2005), pp. 3959-3968
- [14] Hartmann, M., Palzer, S.: Caking of amorphous powders – Material aspects, modelling and applications, *Powder Technol.* 60 (2011), pp. 112-121
- [15] Fatah, N.: Study and Comparison of micronic and nanometric powders: Analysis of physical, flow and interparticle properties of powders, *Powder Technol.* 190 (2009), pp. 41-47

- [16] Shi, L., Feng, Y., Sun, C.C.: Initial moisture content in raw material can profoundly influence high shear wet granulation process, *International Journal of Pharmaceutics* 416 (2011) 1, pp. 43-48
- [17] Hou, H., Sun, C.C.: Quantifying effects of particulate properties on powder flow properties using a ring shear tester, *J. of Pharmaceutical Sciences* 97 (2008) 9, pp. 4030-4039
- [18] Mansa, R.F., Bridson, R.H., Greenwood, R.W., Barker, H., Seville, J.P.K.: Using intelligent software to predict the effects of formulation and processing parameters on roller compaction, *Powder Technology* 181 (2008), pp. 217-225
- [19] Liu, L.X., Marziano, I., Bentham, A.C., Litster, J.D., White, E.T., Howes, T.: Effect of particle properties on the flowability of ibuprofen powders, *International J. of Pharmaceutics* 363 (2008), pp. 109-117